UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/500,647	07/01/2004	Shigeru Sugaya	SONYJP 3.3-1050	2859

530 7590 05/14/2010		

LERNER, DAVID, LITTENBERG,
KRUMHOLZ & MENTLIK
600 SOUTH AVENUE WEST
WESTFIELD, NJ 07090

EXAMINER
ANDREWS, LEON T

ART UNIT	PAPER NUMBER
2462	

MAIL DATE	DELIVERY MODE
05/14/2010	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
Office Action Summary	10/500,647	SUGAYA, SHIGERU
	Examiner	Art Unit
	LEON ANDREWS	2462

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE *3* MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on *05 February 2010*.

2a) ☒ This action is **FINAL**.   2b) ☐ This action is non-final.

3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) *1-30* is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5) ☐ Claim(s) _____ is/are allowed.

6) ☒ Claim(s) *1-30* is/are rejected.

7) ☐ Claim(s) _____ is/are objected to.

8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.

10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a) ☐ All   b) ☐ Some * c) ☐ None of:

      1. ☐ Certified copies of the priority documents have been received.

      2. ☐ Certified copies of the priority documents have been received in Application No. _____.

      3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☐ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☒ Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date *3/17/2010*.

4) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date. _____ .

5) ☐ Notice of Informal Patent Application

6) ☐ Other: _____ .

DETAILED ACTION

1.   **Claims 1-30** are being rejected under 35 U.S.C. 103(a) by Nakada (Patent No.: US

7,133,387 B2) in view of Rakib et al. (Pub. No.: US 2001/0046266 A1) and Brown et al. (Pub.

No.: US 2003/0112776 A1).

Regarding Claim 1, Nakada discloses a wireless communication system operating without a

base station and including (Fig. 16, wireless system network apparatus, column 1, line 46;

transmission and reception of a packet when apparatus A transmits data to apparatus B which

shares the media with apparatus A, column 1, lines 54-56) a plurality of communication

apparatuses (Figs. 1A and 1B, mobile communications system with communication terminals 2,

3 and 4, column 3, lines 40-42) associated with respective communication areas, the system

comprising:

an information transmission source communication apparatus (Fig. 6, 44, transmission

unit) for forming a data packet (correlations between prescribed preamble signals, column 4,

lines 6-8) by inserting a preamble signal (Fig. 5, 28, preamble signal) into each transmission data

and transmitting the formed data packet (Fig. 6, transmission unit 44 modulates and transmits

preamble packets and data generated by downstream signal generation unit 45, column 1, lines

41-44) to one or more of the communication apparatuses that are located within the

communication area of the transmission source communication apparatus; and

a communication apparatus (Fig. 1A, terminal 2) located within the communication area

of the transmission source communication apparatus and not currently communicating (message

part and acknowledgement are given for terminal 3 which transmitted preamble 6 but not to

terminal 2, column 4, lines 61-66) for recognizing that the transmission path is used for a

predetermined interval (prescribed delay time period of the preamble signal, column 4, lines 36-

37) by another communication apparatus from a time (time period of the preamble signal,

column 4, lines 36-37) when the preamble signal is detected (determines whether a preamble was

received, column 4, line 23-24);

Nakada fails to disclose a communication system without a base station and a preamble

signal inserted in transmission packet so as to be integral with each transmission data.

But, Rakib et al. discloses bidirectional communication system having a central unit

transmitter and a remote unit receiver, paragraph [0016], page 2, lines 1-77, and preamble data

(signal) must be inserted into every timeslot's data to correct (be integral with) the phase and

amplitude of the signals (transmission data) for that timeslot, paragraph [0311], page 29, lines

10-13.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time

the invention was made to use Rakib et al.'s communication system without a base station and a

preamble signal inserted in transmission packet so as to be integral with each transmission data

because this would have allowed the central unit to receive downstream data and the remote unit

to receive local carrier signal, paragraph [0016], page 2, lines 3-9, and, the insertion of preamble

data (signal) into every data (transmission data) and for the correction of (be integral with) the

carrier signal for that timeslot [0311], page 29, lines 10-13.

The combination Nakada and Rakib et al. fails to disclose an apparatus not currently communicating engaging in wireless communication over the transmission path when it does not detect any preamble signal.

But, Brown et al. discloses no detection of the preamble signal on one or more multipath, mobile station signal detection is declared and message is sent to the mobile station, paragraph [0063], page 7, lines 6-10.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to use Brown et al.'s apparatus not currently communicating engaging in wireless communication over the transmission path when it does not detect the preamble signal because this would have allowed the detection of a mobile station signal with a message sent to the mobile station when there was no detection of the preamble signal, paragraph [0063], page 7, lines6-10.

Regarding Claim 2, Nakada discloses the wireless communication system as claimed in claim 1, wherein

the information transmission source communication apparatus forms the data packet at a predetermined time unit (Fig. 2, 16, delay memory unit), and further comprising:

an information reception target communication apparatus (Fig. 2, 15, code generation unit 15) for generating acknowledge (ACK) information in response to the success in correctly receiving the data and for generating not acknowledge (NACK) information (Fig. 2, 15, code generation unit 15 generates ACK signal or NACK signal on the basis of the output from the preamble determination unit 14, column 4, lines 32-34; Fig. 3) in response to a failure in

correctly receiving the data (Fig. 2, 14, preamble determination unit 14 determines whether a

preamble was received or not (failure), column 4, lines 23-24), forms an ACK (Fig. 3, ACK

signal 8 for allowing to use the message part is transmitted for preamble signal 6, column 4, lines

65-66) or NACK packet to which a preamble signal is inserted, and returns it, just after the

reception of the data packet (Fig. 3, S26, message part available at terminal 3, column 4, line 67);

said information transmission source communication apparatus retransmits the data

packet of said predetermined time unit in response to the reception of the NACK packet (Fig. 3,

NACK signal 7 for rejecting to use the message part is transmitted for preamble signal 5 at

terminal 2, column 5, lines 1-2); and

said communication apparatus not currently communicating recognizes a use of the

transmission path for retransmission (terminal 3 which is allowed to use the message part can

now transmit and receive data, column 5, line 4-6) based on the reception of the preamble signal

for a period (time period of the preamble signal, column 4, lines 36-37) from the detection of the

NACK packet to detection of the next ACK packet.

Regarding Claim 3, Nakada discloses the wireless communication system as claimed in claim

2, wherein

other communication apparatuses not currently communicating (Fig. 3, terminal 3)

recognize the termination of the use of the transmission path (Fig. 3, S26, message part

available) when the ACK packet cannot be detected (Fig. 3, ACK 11) based on the detection of

the preamble signal (Fig. 5, 28, preamble signal) until a predetermined elapsed time (prescribed

delay time period of the preamble signal for NACK, column 4, lines 36-37) from when the

NACK packet is received (Fig. 3, NACK 12).

Regarding Claim 4, Nakada discloses the wireless communication system as claimed in claim

2, wherein

the information reception target communication apparatus adds the preamble signal to a

top (control signal of which the header designates a base station, column 1, lines 24-25) of a

beacon signal (base station transmits a free channel signal (beacon signal) for allowing the

mobile station to transmit the control signal and an identifier for the base station, column 1, lines

25-27) describing information regarding a communication apparatus (mobile station, column 1,

line 23) of which transmission is permitted with priority (data items from the communications

terminals are determined and priorities are setup, column 1, lines 38-40), and transmits the

beacon signal;

the communication apparatus specified by the beacon signal transmits a predetermined

unit of data packet (data items from the communication terminals are determined and two-step

priorities are set up on the basis of the determination result, column 1, lines 38-40) when there is

data to be transmitted to said information reception target apparatus; and

other communication apparatuses (Fig.3, terminal 4) not currently communicating

recognize based on the detection of the preamble signal the use of the transmission path for the

time interval (prescribed delay time period of the preamble signal, column 4, lines 36-37)

corresponding to the packet length (communication terminal 30 receives the down stream

standard signal which is as long as the preamble, column 1, lines 45-49) from when said beacon

signal is received.

Regarding Claim 5, Nakada discloses the wireless communication system as claimed in claim

2, wherein

said information transmission source communication apparatus transmits a transmission

request packet (RTS) into which the preamble signal is inserted when no preamble signal is

detected for a predetermined time interval (prescribed delay time period of the preamble signal,

column 4, lines 36-37); and

said information reception target communication apparatus returns a confirmation notice

packet (CTS) (data packet is confirmed, column 1, line 36) in response to the reception of a

transmission request packet (RTS) (packet with preamble and data is modulated by a short

period, column 1, lines 64-65).

Regarding Claim 6, Nakada discloses the wireless communication system as claimed in claim

5, wherein

said other communication apparatus not currently communicating recognizes based on

the detection of the preamble signal the use of the transmission path from when the NACK

packet is detected (Fig. 3, NACK 12), during a predetermined interval (Fig. 3, interval between

NACK 12 and ACK 11) from the reception of the confirmation notice (CTS) packet (data packet

is confirmed, column 1, line 36), to when the next ACK packet is detected (Fig. 3, ACK 11).

Regarding Claim 7, Nakada discloses the wireless communication system as claimed in claim

5, wherein

said information source communication apparatus makes the data packet include therein

an element (channel number for a data packet, column 1, lines 35-36) of the transmission request

(RTS) for a next data packet transmission (channel allocation is controlled and data items are

determined for competitive (transmitting) terminals, column 1, lines 36-39) when transmission

data exists.

Regarding Claim 8, Nakada discloses the wireless communication system as claimed in claim

5, wherein

said information reception target communication apparatus makes the ACK packet (Fig.

3, ACK 11) or the NACK packet corresponding to the received data packet include an element of

confirmation notice (CTS) (data packet is confirmed, column 1, line 36).

Regarding Claims 9 and 20 Nakada discloses a wireless communication apparatus (Figs. 1A

and 1B, terminals 2, 3, 4) and method (method for channel access, column 1, lines 7-8) operating

within a communication system not having a base station (Fig. 16, wireless system network

apparatus, column 1, line 46; transmission and reception of a packet when apparatus A transmits

data to apparatus B which shares the media with apparatus A, column 1, lines 54-56) and

including a plurality of communication apparatuses (Figs. 1A and 1B, mobile communications

system with communication terminals 2, 3 and 4, column 3, lines 40-42) associated with

respective communication areas, comprising:

buffer means (Fig. 2, 16, delay memory unit) for dividing transmission data by a

predetermined unit (Fig. 2, 14, preamble determination unit for determining whether or not to

transmit signals, column 3, lines 3-5);

transmission data processing means (Fig. 2, 13, correlation unit) for adding a

predetermined preamble signal (calculates correlations between prescribed preamble signals,

column 4, lines 6-8) to divided transmission data from the buffer means to form a transmission

packet (preamble packets and data generated by downstream signal generation unit 45, column 1,

lines 42-44);

preamble detection means (Fig. 2, 14) for detecting a preamble signal (determines

whether a preamble was received, column 4, line23-24) on a transmission path (Fig. 5, RACH,

random access channel); and

transmission means (Fig. 6, 44) for transmitting the formed packet when no preamble

signal is detected for a predetermined interval (prescribed delay time period of the preamble

signal, column 4, lines 36-37) at said preamble detection means, the formed packet being

transmitted to one or more communication apparatuses (Figs. 1A and 1B, terminals 2, 3, 4)

within the communication area of the communication apparatus transmitting the packet,

whereby a communication apparatus (Fig. 1A, terminal 2) located within the

communication area of the communication apparatus transmitting the packet and not currently

communicating (message part and acknowledgement are given for terminal 3 which transmitted

preamble 6 but not to terminal 2, column 4, lines 61-66) recognizes that the transmission path

(Fig. 5, RACH, random access channel) is used for a predetermined interval (prescribed delay

time period of the preamble signal, column 4, lines 36-37) by another communication apparatus

from a time (time period of the preamble signal, column 4, lines 36-37) when the preamble

signal is detected (determines whether a preamble was received, column 4, line23-24).

Nakada fails to disclose a communication system without a base station and a preamble

signal inserted in transmission packet so as to be integral with each transmission data.

But, Rakib et al. discloses bidirectional communication system having a central unit

transmitter and a remote unit receiver, paragraph [0016], page 2, lines 1-77, and preamble data

(signal) must be inserted into every timeslot's data to correct (be integral with) the phase and

amplitude of the signals (transmission data) for that timeslot, paragraph [0311], page 29, lines

10-13.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time

the invention was made to use Rakib et al.'s communication system without a base station and a

preamble signal inserted in transmission packet so as to be integral with each transmission data

because this would have allowed the central unit to receive downstream data and the remote unit

to receive local carrier signal, paragraph [0016], page 2, lines 3-9, and, the insertion of preamble

data (signal) into every data (transmission data) and for the correction of (be integral with) the

carrier signal for that timeslot [0311], page 29, lines 10-13.

The combination Nakada and Rakib et al. fails to disclose an apparatus not currently

communicating engaging in wireless communication over the transmission path when it does not

detect any preamble signal.

But, Brown et al. discloses no detection of the preamble signal on one or more multipath,

mobile station signal detection is declared and message is sent to the mobile station, paragraph

[0063], page 7, lines 6-10.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time

the invention was made to use Brown et al.'s apparatus not currently communicating engaging in

wireless communication over the transmission path when it does not detect the preamble signal

because this would have allowed the detection of a mobile station signal with a message sent to

the mobile station when there was no detection of the preamble signal, paragraph [0063], page 7,

lines6-10.

Regarding Claims 10 and 21, Nakada discloses the wireless communication apparatus and

method, further comprising:

reception means (Fig. 6, 33, receiving unit) for receiving a signal added to the preamble

signal (preamble signal and transmission data, column 2, lines 65-66) in response to the detection

of the preamble signal; and

reception data processing means (Fig. 3, base station 1) for analyzing the signal

(transmitter/receiver in the base station analyses the signal sequence of the preamble, column 3,

lines 59-62) received by said reception means.

Regarding Claims 11 and 22, Nakada discloses the wireless communication apparatus and method, wherein

said reception data processing means generates acknowledge (ACK) information (Fig. 3, ACK 8) in response to correctly receiving a for-own-station data (transmission data, column 2, line 66) and not acknowledge (NACK) information (Fig. 3, NAK 7) in response to incorrectly receiving the for-own-station data;

said transmission data processing means forms an ACK packet (Fig. 3, ACK 11) or an NACK packet (Fig. 3, NACK 12) into which a preamble signal (preamble signal, column 2, line 65) is inserted; and

said transmission means transmits the ACK packet (Fig. 3, ACK 11) or the NACK packet (Fig. 3, NACK 12) just after the reception of the data.

Regarding Claims 12 and 23, Nakada discloses the wireless communication apparatus and method, wherein

upon not currently communicating (the base station stops transmitting knowing immediately that the mobile station is in its zone, column 1, lines 29-31), said reception data processing means recognizes use of the transmission path for the data retransmission from when the NACK packet is detected to when the next ACK packet is detected (Fig. 3, ACK 11).

Regarding Claims 13 and 24, Nakada discloses the wireless communication apparatus and method, wherein

said reception data processing means recognizes a termination of use (the base station stops transmitting knowing immediately that the mobile station is in its zone, column 1, lines 29-31) of the transmission path when no ACK packet (Fig. 3, ACK 11) is detected until a predetermined interval (prescribed delay time period of the preamble signal for NACK, column 4, lines 36-37) has elapsed from when the NACK packet (Fig. 3, NACK 12) is received.

Regarding Claims 14 and 25, Nakada discloses the wireless communication apparatus and method, wherein

said transmission data processing means generates a beacon signal (base station transmits a free channel signal (beacon signal) for allowing the mobile station to transmit the control signal and an identifier for the base station, column 1, lines 25-27) describing information regarding a communication apparatus (mobile station, column 1, line 23) from which transmission is permitted with priority (data items from the communications terminals are determined and priorities are setup, column 1, lines 38-40); and

said reception data processing means analyzes (transmitter/receiver in the base station analyses the signal sequence of the preamble, column 3, lines 59-62) whether the transmission of its own station (preamble signal and transmission data, column 2, lines 65-66) is permitted with priority by analyzing (transmitter/receiver in the base station analyses the signal sequence of the preamble, column 3, lines 59-62) the beacon signal.

Regarding Claims 15 and 26, Nakada discloses the wireless communication apparatus and method, wherein

upon not currently communicating (the base station stops transmitting knowing

immediately that the mobile station is in its zone, column 1, lines 29-31), said reception data

processing means recognizes use of a transmission path (Fig. 5, RACH) for a time interval

(prescribed delay time period of the preamble signal, column 4, lines 36-37) corresponding to the

packet length (communication terminal 30 receives the down stream standard signal which is as

long as the preamble, column 1, lines 45-49) from when the beacon signal is received.

Regarding Claims 16 and 27, Nakada discloses the wireless communication apparatus and

method, wherein

said transmission data processing means generates a transmission request (RTS) packet

(packet with preamble and data is modulated by a short period, column 1, lines 64-65) for a data

transmission target (Fig.3, terminal 4);

and in response to reception of the transmission request (RTS) packet from another

communication apparatus (Fig.3, terminal 4) by said reception processing means, said

transmission data processing means generates a confirmation notice (CTS) packet (data packet is

confirmed, column 1, line 36).

Regarding Claims 17 and 28, Nakada discloses the wireless communication apparatus and

method, wherein

upon not currently communicating (the base station stops transmitting knowing

immediately that the mobile station is in its zone, column 1, lines 29-31), said reception data

processing means recognizes use of a transmission path (Fig. 5, RACH) from when a not

acknowledge (NACK) packet (Fig. 3, NACK 12) is detected, during a predetermined interval

(prescribed delay time period of the preamble signal, column 4, lines 36-37) from the reception

of the confirmation notice (CTS) packet (data packet is confirmed, column 1, line 36), to when a

next acknowledge (ACK) packet (Fig. 3, ACK 11) is detected.

Regarding Claims 18 and 29, Nakada discloses the wireless communication apparatus and

method, wherein

said transmission data processing means makes the data packet include therein an

element (channel number for a data packet, column 1, lines 35-36) of the transmission request

(RTS) for a next data packet transmission (channel allocation is controlled and data items are

determined for competitive (transmitting) terminals, column 1, lines 36-39) when a following

transmission data (transmission data, column 2, line 66) exists.

Regarding Claims 19 and 30, Nakada discloses the wireless communication apparatus and

method, characterized in that:

said transmission data processing means makes an acknowledge (ACK) packet (Fig. 3,

ACK 11) or a not acknowledge (NACK) packet (Fig. 3, NACK 12) corresponding to the

received data packet include an element (channel number for a data packet, column 1, lines 35-

36) of the confirmation notice (CTS) (data packet is confirmed, column 1, line 36) therein.

Response to Arguments

2.   Applicant's arguments filed February 5, 2010 have been considered as follows:

- In the remarks on page 17 of the amendment, applicant contends that Nakada, Rakib et al. or Brown et al. fails to disclose or suggest a communication apparatus located within the communication area of the transmission source communication apparatus and not currently communicating for recognizing that the transmission path is used for a predetermined interval by another communication apparatus from a time when the preamble signal is detected.

- The examiner respectfully maintains the prior prosecution and contends that with the amendment to the claim limitation, Nakada further discloses a CDMA system channel access control wherein the base station connected to a plurality of mobile stations, transmits an allowance signal towards a mobile station, but during the propagation time of the preamble signal, transmits a rejections signal towards another mobile station which transmits the preamble signal, column 2, lines 49-61.

Conclusion

3.   Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after

the end of the THREE-MONTH shortened statutory period, then the shortened statutory period

will expire on the date the advisory action is mailed, and any extension fee pursuant to 37

CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event,

however, will the statutory period for reply expire later than SIX MONTHS from the date of this

final action.

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Leon Andrews whose telephone number is (571) 270-1801. The

examiner can normally be reached on Monday through Friday 7:30 AM to 5:00 PM EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Rao S. Seema can be reached on (571) 272-3174. The fax phone number for the

organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would

like assistance from a USPTO Customer Service Representative or access to the automated

information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

LA/la
May 5, 2010
/Seema S. Rao/
Supervisory Patent Examiner, Art Unit 2462